

LPK TOILET SEAT DISINFECTING FOAM - D1617



SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : LPK TOILET SEAT DISINFECTING FOAM

Product code : D1617.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Disinfectant product

1.3. Details of the supplier of the safety data sheet

Registered company name : GOJO Industries-Europe Ltd.

Address : Units 5 & 6, Stratus Park.MK10 0DE.Brinklow, Milton Keynes.England.

Telephone : +44(0) 1908588444. Fax : +44(0) 1908588445.

infoUK@gojo.com

1.4. Emergency telephone number : +44 (0) 333 333 9962.

Association/Organisation : .

<http://echa.europa.eu/fr/support/helpdesks/national-helpdesks/list-of-national-helpdesks>

Other emergency numbers

Belgique, België, Belgien / Lëtzebuerg, Luxemburg, Luxembourg : Centre Anti-Poisons/Antigifcentrum: 0032 (0)70 245 245

Österreich : Vergiftungsinformationszentrale Vienna: +43 1 406 43 43

Deutschland : Giftnotruf Berlin: +49 30 19240

Bulgaria : Emergency Medical Institute Pirogov: +359 2 9154 409

Hrvatska : Poison Control Centre Zagreb: +358 1 2348 342

Danmark : Poison Hotline, Bispebjerg Hospital: + 45 82 12 12 12

España : Teléfono Instituto Nacional de Toxicología: +34 91 562 04 20

Eesti : Estonian Poison Information Centre: +372 62 69 379

Suomi, Finland : Finland Poison Information Centre:+358 9 471 977

Greece : Poisons Information Centre: +30 21 07 79 37 77

Magyarország : Health Toxicological Information Service: +36 80 20 11 99

Ireland, Éire : Ireland National Poisons Information Centre: +353 1 8379964

Ísland : Iceland Poison Information Centre: +354 525 111, +354 543 2222

Italia : Centro Antiveleni, Roma: +39 06 305 4343

Latvija : Latvian Poisons Information Centre: +371 6704 2473

Lietuva : Apsinuodijimu kontroles ir informacijos biuras: +370 2 36 20 52, +370 687 53378

Malta : Mater Dei Hospital: + 356 21450000

Norge, Noreg : Norway Poisons Information:+ 47 22 591300

Nederland : Nationaal Vergiftigingen Informatie Centrum: +31 30 274 88 88

Polska : Poland Poison Control and Information Centre, Warsaw: +48 22 619 66 54, +48 22 619 08 97

Portugal : Centro de Informação Antivenenos: +351 21 330 3284

România : Spitalul de Urgenta Floreasca: +40 21 230 8000

United Kingdom : Guy's & St Thomas' Poisons Unit, London: +44 870 243 2241

Slovensko : National Toxicological Information Centre : +421 2 54 77 4 166

Slovenija : Poison Centre: + 386 41 650 500

Sverige : Giftinformationscentralen, Stockholm: +46 8 33 12 31

Schweiz, Suisse, Svizzera, Svizra : Swiss Toxicological Information Centre: +41 44 251 51 51

Cesko : Toxicological Information Centre: +420 22 49 192 93

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present a health hazard with the exception of possible occupational exposure thresholds (see paragraphs 3 and 8).

LPK TOILET SEAT DISINFECTING FOAM - D1617

2.2. Label elements

Biocidal mixture (see section 15).

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard statements :

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements - Prevention :

P273 Avoid release to the environment.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 64-17-5 EC: 200-578-6 REACH: 01-2119457610-43 ETHANOL	GHS07, GHS02 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319	[1]	$2.5 \leq x \% < 10$
CAS: 85409-22-9 EC: 287-089-1 BENZALKONIUM CHLORIDE	GHS07, GHS05, GHS09 Dgr Acute Tox. 4, H302 Skin Corr. 1B, H314 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1		$0 \leq x \% < 1$
CAS: 18472-51-0 EC: 242-354-0 REACH: 01-2119946568-22 CHLORHEXIDINE DIGLUCONATE	GHS05, GHS09 Dgr Eye Dam. 1, H318 Aquatic Acute 1, H400 M Acute = 10 Aquatic Chronic 1, H410 M Chronic = 1		$0 \leq x \% < 1$

(Full text of H-phrases: see section 16)

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of splashes or contact with eyes :

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Keep eye wide open while rinsing.

In the event of swallowing :

Seek medical attention, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

LPK TOILET SEAT DISINFECTING FOAM - D1617

In the event of a fire, use :

- carbon dioxide (CO₂)
- powder
- foam
- dry sand

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

No data available.

Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5		1000 ppm		A3	

LPK TOILET SEAT DISINFECTING FOAM - D1617

- Germany - AGW (BAuA - TRGS 900, 29/01/2018) :

CAS	VME :	VME :	Excess	Notes
64-17-5		500 ppm 960 mg/m ³		2(II)

- Belgium (Arrêté du 09/03/2014, 2014) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 ppm 1907 mg/m ³				

- Denmark (2008) :

Stof	TWA	VSTEL	Loftvaerdi	Anm
64-17-5	1000 ppm 1900 mg/m ³			

- France (INRS - ED984 :2016) :

CAS	VME-ppm :	VME-mg/m ³ :	VLE-ppm :	VLE-mg/m ³ :	Notes :	TMP No :
64-17-5	1000	1900	5000	9500	-	84

- Finland (HTP-värden 2016) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 ppm 1900 mg/m ³	1300 ppm 2500 mg/m ³			

- Spain (Instituto Nacional de Seguridad e Higiene en el Trabajo (INSHT), 2017) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5		1.000 ppm 1910 mg/m ³		s	

- Ireland (Code of practice for the Chemical Agents Regulations, 2016) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5		1000 ppm			

- Norway (Veiledning om administrative normer for forurensning i arbeidsatmosfære, May 2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	500 ppm 950 mg/m ³				

- Netherlands / MAC-waarde (10 december 2014) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	260 mg/m ³	1900 mg/m ³		Huid	

- Poland (2014) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1900 mg/m ³				

- Czech Republic (Regulation No. 361/2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 mg/m ³	3000 mg/m ³		I	

- Slovakia (Règlement 300/2007, 471/2011 23/11/2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	500 ppm 960 mg/m ³	1 000 ppm 1 920 mg/m ³			

- Switzerland (SUVAPRO 2017) :

CAS	VME	VLE	Valeur plafond	Notations
64-17-5	500 ppm 960 mg/m ³	1000 ppm 1920 mg/m ³		SSC

- Sweden (AFS 2015 :7) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1993 ppm 500 mg/m ³ 1000 fcm ³	1000 mg/m ³ 1900 fc/m ³		V	

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 ppm 1920 mg/m ³	- ppm - mg/m ³			

- Bulgare

?????? ?????	???????? ?????????? 8 ????	???????? ?????????? 15 min	????????	?????????? ??????	
64-17-5	1000 mg/m ³				

LPK TOILET SEAT DISINFECTING FOAM - D1617

- Estonie

Identification	Piirnorm	Luhiajalise kokkupuute piirnorm	Piirnormi lagi	Markused
64-17-5	500 ppm 1000 mg/m3	1000 ppm 1900 mg/m3		

- Greece (90/1999) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5		1000 ppm 1900 mg/m3			

- Hongrie

Megnevezes	AK-ertekek	CK- ertekek	MK- ertekek	Megjegyzések
64-17-5	1900 mg/m3	7600 mg/m3		

- Latvia (Regulation No. 325/2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 mg/m3				

- Romania (Hotărâre 1218/2006) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 ppm 1900 mg/m3	5000 ppm 9500 mg/m3			

- Slovenia (Uradni List, 04/06/2015) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5		1000 ppm 1900 mg/m3		Y	

- Croatia

Identification	TWA	STEL	Ceiling	Notations
64-17-5	1000 ppm 1900 mg/m3			F

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

- Body protection

Work clothing worn by personnel shall be laundered regularly.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state :	Fluid liquid.
Color:	colourless
Odour:	mint-like

Important health, safety and environmental information

pH :	5.50 +/- 1. Neutral.
Flash Point :	62.00 °C.
Vapour pressure (50°C) :	Not relevant.
Density :	0.989 - 1.000
Water solubility :	Soluble.

9.2. Other information

No data available.

LPK TOILET SEAT DISINFECTING FOAM - D1617

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid :

- frost

10.5. Incompatible materials

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

No data available.

11.1.1. Substances

No toxicological data available for the substances.

11.1.2. Mixture

No toxicological data available for the mixture.

SECTION 12 : ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

CHLORHEXIDINE DIGLUCONATE (CAS: 18472-51-0)

Fish toxicity : LC50 = 2.08 mg/l

Crustacean toxicity : EC50 = 0.087 mg/l
Factor M = 10
Species : Daphnia magna

NOEC = 0.02 mg/l
Factor M = 1
Species : Daphnia magna

Algae toxicity : ECr50 = 0.081 mg/l
Factor M = 10

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

CHLORHEXIDINE DIGLUCONATE (CAS: 18472-51-0)

Biodegradability : Rapidly degradable.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

LPK TOILET SEAT DISINFECTING FOAM - D1617

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number

-

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

-

14.4. Packing group

-

14.5. Environmental hazards

-

14.6. Special precautions for user

-

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2016/1179. (ATP 9)

- Container information:

No data available.

- Particular provisions :

No data available.

- Labelling for biocidal products (Regulation 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC)

:

Name	CAS	%	Product-type
CHLORHEXIDINE DIGLUCONATE	18472-51-0	1.20 g/kg	01 02
BENZALKONIUM CHLORIDE	85409-22-9	3.00 g/kg	01 02
ETHANOL	64-17-5	48.00 g/kg	01 02

Product-type 1 : Human hygiene.

Product-type 2 : Disinfectants and algacides not intended for direct application to humans or animals.

15.2. Chemical safety assessment

No data available.

LPK TOILET SEAT DISINFECTING FOAM - D1617

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.